

How to use ASTA 3000 Engine Treatment

How?

1. Turn off the engine
2. Pour the content of ASTA 3000 Engine Treatment bottle number 1 into the fuel tank, no matter what the current fuel level is
3. Pour the content of ASTA 3000 Engine Treatment bottle number 2 into the engine oil (an oil change isn't necessary)

Which engines?

ASTA 3000 Engine Treatment is compatible with any engine, old or new; gasoline, diesel or LPG; with or without a catalytic converter, turbo, multi-valve, including today's most modern engines.

How often?

We recommend the use of ASTA 3000 Engine Treatment every 30,000 kilometres (20,000 miles) or at least once a year.

How much?

Cubic capacity	Quantity
Up to 3,000 cm ³	75 ml into the fuel 75 ml into the engine oil
From 3,000 to 5,000 cm ³	250 ml into the fuel 250 ml into the engine oil
From 5,000 to 10,000 cm ³	500 ml into the fuel 500 ml into the engine oil
From 10,000 to 30,000 cm ³	1000 ml into the fuel 1000 ml into the engine oil
Above 30,000 cm ³	2000 ml into the fuel 2000 ml into the engine oil

ASTA 3000 Engine Treatment is also suitable for trucks, buses, boats, motorbikes, lawn mowers, and small tools.

Trucks, buses: Follow the recommendations according to the engine's cubic capacity.

Motorbikes: For two-stroke engines: pour half the content of bottle 1 and half the content of bottle 2 into a full fuel tank. Pour the other half of the two bottles 500 km later.

For four-stroke engines: follow usual procedure.

Boats: For two-stroke engines: pour the content of bottle 1 and the content of bottle 2 into a full fuel tank.

For four-stroke engines: follow the usual procedure.

Lawn mowers and small tools: Pour half the content of bottle 1 and half the content of bottle 2 into a full fuel tank. Pour the other half of the two bottles' contents six months later.